

MSDS UltraShield Composite Decking

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: UltraShield Composite Decking

DESCRIPTION: Polyethylene Co-Extrusion

ITEM #: Not Established

APPEARANCE AND ODOR: Composite Wood, Faint Odor

SUPPLIER:

NewTechWood Ltd.

19111 Walden Forest Dr. Suite B, Humble, TX 77346 USA

Telephone: 281-570-6450

China Factory: Huidong Meixin Plastic Lumber Products Manufacturing Co., Ltd

NGA Industrial Park, Daling, Huidong, Guangdong, PRC. 516321

Telephone: 86-752-8138888

2. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAMES AND SYNONYMS:

1. WOOD FIBER

2. POLYETHYLENE

INGREDIENTS CONSIDERED HAZARDOUS TO HEALTH:

SUBSTANCE NAME	WEIGHT PERCENTAGE
WOOD FIBER	60 - 65%
POLYETHYLENE	35 - 10%

NOTE: WOOD FIBER IS CONTAINED IN A POLYETHYLENE MATRIX. POLYETHYLENE IS A THERMOPLASTIC MATERIAL. THIS MATRIX CONTAINS PREDOMINANTLY WOOD FIBER AND POLYETHYLENE. THE POLYETHYLENE IS SOURCED MAINLY FROM RECLAIMED/RECYCLED PLASTIC BOTTLES AND GROCERY FILM; WOOD FIBER IS SOURCED FROM RECLAIMED/RECYCLED SAW DUST, FURNITURE, AND WASTE PALLETS.

3. HAZARD IDENTIFICATION

U.S. OSHA HAZARD COMMUNICATION STANDARD: This product may be used in application that produce wood dust fibers. According to OSHA 29 CFR 1910.1200, certain wood fibers and carbon black are considered hazardous if the workplace airborne concentrations exceeds the OSHA or ACGIH exposure limits (see section 8).

EMERGENCY RESPONSE DATA: Gray, teak, and red solid. Exposure to fire can generate toxic fumes. High dust levels may create potential for explosion. DOT ERG No. NA

4. FIRST AID MEASURES

EYE CONTACT: Flush thoroughly with water. If irritation occurs, call a physician.

SKIN CONTACT: Wash contact areas with soap and water. Launder contaminated clothing before reuse.

INHALATION: If respiratory irritation, cough, shortness of breath, wheezing or chest tightness occurs after exposure to dust, remove from further exposure, seek immediate medical assistance and call for a physician.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water

SPECIAL FIRE FIGHTING PROCEDURES: Use water to keep fire exposed product cool. For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

SPECIAL PROTECTIVE EQUIPMENT: For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to fire can generate toxic fumes. High dust levels may create potential for explosion. Flash Point C(F): > 370 (698) (Flame Spread Index = 80). Flammable limits - LEL: NA, UEL: N/A.

6. ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURE: None

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: Where dusty conditions are created as a result of cutting or sawing, wet down material then sweep or vacuum for disposal. Personnel performing cleanup must use protective equipment.

ENVIRONMENTAL PRECAUTIONS: Not expected to be a problem.

7. HANDLING AND STORAGE

HANDLING: NewTechWood Decking is not intended for load-bearing or heavy structural applications. Please consult NewTechWood company literature for proper usage. The density of NewTechWood's composite lumber is heavier than compared to most traditional lumber products. Therefore, the user must employ the proper handling to prevent damage or injury. Do not burn in fireplace or use firewood.

STORAGE: Store NewTechWood Decking away from strong oxidizing agents or combustible material. Do not store in open or unlabeled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION: Use in well ventilated area

RESPIRATORY PROTECTION: Approved dust respirators must be used for dusty conditions or if breathing of dusts is likely.

EYE PROTECTION: Safety glasses with side shields, or goggles, should be worn to protect against dust particles.

SKIN PROTECTION: No special equipment required. Good personal hygiene practices should always be followed.

SUBSTANCE NAME	SOURCE	TWA (ppm mg / m3)	STEL (ppm mg / m3)
Wood Fiber Dust			
Hardwood	OSHA	5	
Softwood	OSHA	5	
Softwood	ACGIH		10

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical properties are given which are considered representative. For specific physical properties refer to the Product Data Sheet.

APPEARANCE: Solid

COLOR: Red

Gray

ODOR: None

PH VALUE: N/A

BOILING POINT: N/A

MELTING POINT: Approximately 131 C

FLASH POINT: 399 C

FLAMMABILITY: SwRI - Flame Spread Index = 115

SELF IGNITION: 437 C

SMOKE DEVELOPED VALUE: 135

WATER ABSORPTION: 0.12% by weight

COEF. OF MOISTURE EXPANSION: 0.11% by weight

WATER SOLUBILITY: Negligible

FUNGUS RESISTANCE: No Decay

VAPOR DENSITY: NE

EVAPORATION RATE: NE

POUR POINT: NA

FREEZING POINT: NE

VOLATILE ORGANIC COMPOUND: NE

10. STABILITY AND REACTIVITY

STABILITY (THERMAL, LIGHT, ETC.): Stable.

CONDITIONS TO AVOID: Heat and flame. Build up of dusts.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Smoke, Carbon Monoxide, Acetaldehyde, Formaldehyde, Formic Acid, Acetic Acid.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL DATA

ACUTE TOXICOLOGY

Oral Toxicity (Rats): Not established.
Dermal Toxicity (Rabbits): Not established.
Inhalation Toxicity (Rats): Not established.
Eye Irritation (Rabbits): Not established.
Skin Irritation (Rabbits): Not established.

CHRONIC TOXICOLOGY

IARC has determined and summarized that there is sufficient evidence to classify wood fiber as a human carcinogen. Exposure to wood fiber is severely reduced when wood fiber is encased by a polymer matrix.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND EFFECTS: Not Established

13. DISPOSAL CONSIDERATION

WASTE DISPOSAL: Dispose of waste as normal refuse.

14. TRANSPORT INFORMATION

USA DOT: Not regulated by US DOT.

IMO: Not regulated by IMO.

15. REGULATORY INFORMATION

GOVERNMENT INVENTORY STATUS: All components comply with TSCA.

U.S. SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) TITLE III: This product contains no "EXTREMELY HAZARDOUS SUBSTANCES."

USE: Composite Lumber Products for Decking

INGREDIENTS:

Wood fiber	60 - 65% by weight
Polyethylene	35 - 40% by weight

The provided information is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; the user therefore assumes all risks of use of the product and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by US law, republication or retransmission of this document, in whole or in part, is not permitted. Huidong Meixin Plastic Lumber Products Manufacturing Co., Ltd. assumes no responsibility for accuracy of information unless the document is the most current available from an official member of Huidong Meixin Plastic Lumber Products Manufacturing Co., Ltd.'s distribution network. Huidong Meixin Plastic Lumber Products Manufacturing Co., Ltd. neither represents nor do warrants that the format, content or product formula contained in this document complies with the laws of any other country except the United States of America.